# HTC200



## PERFORMANCE CRITERIA FOR HTC200 TURBO COMPRESSOR

For correct operation of this unit, the following maximum conditions must not be exceeded :-

Airflow	720-4560m3/h
Pressure	1200-2000mbar
Axial power	150kW
VDF Voltage	380 - 480V
VDF Frequency	50 - 60Hz


#### **CONTROL / INSTRUMENTATION**

Type of Controller	PLC
Network to SCADA, MCP	Standard : MODBUS TCP/IP and MODBUS RTU Optional : PROFIBUS-DP and ETHERNET IP
Input	Analog : 4~20 mA or 0~10v / digital : Dry contact
Output	Analog : 4~20 mA or 0~10v / digital : Relay (2A)
Interface	7" Touchscreen

Drocouro ratio	Absolute outlet pressure
Pressure ratio =	Absolute inlet pressure

Normal (sea level) ambient conditions are 1013 mbar & 15 deg C.

A BLOWER is a unit in which the inlet pressure is substantially equal to the ambient pressure.







LEFT SIDE VIEW





## **UNIQUE FEATURES**

- \* Around 20% more energy efficient than PD blowers
- \* Noise levels are typically around 75-80dB(A)
- \* 100% lubricant free due to air foil bearings
- \* Compact size and light weight compared to PD blowers
- \* Low maintenance, no lubricants only filter change needed

### **SPECIFICATION**

**PMS motors:** Are optimised for high speed rotation, minimising current loss and delivering a maximum efficiency of 98%. No power loss due to direct drive. Stop-start test conducted over 100,000 times.

**Air Foil bearings:** Are 100% lubricant free, contactless and eco-friendly. Special coating reduces frictional wear providing long service life. No maintenance needed.

**Impeller:** Made from high strength heat treated aluminium. Manufactured with state-of-the-art aerodynamic technology. High precision 5-axis machining ensures wide flow range and surge margin. Anodised coating enhances surface strength.

**Cooling System:** Self-cooling system so no separate power source required. No maintenance required.

**Inverter:** Less than 1% starting current. 0.3% Unload Power Consumtion. KEB (Knetic Energy Back-up) function for enhanced safety in case of power failure.

All blowers are individually tested. Test certificates will be

issued if requested. A comprehensive Installation and Operating Instruction

folder is supplied with every blower.

Size: 1033 (w) x 2050 (l) x 1697 (h)

Dimensions in millimetres (inch conversions in brackets)